

# 3.96mm(.156") Wire To Wire And Wire To Board Connector






## SPECIFICATIONS:

- Current Rating:7A AC,DC
- Voltage Rating:600V AC,DC
- Operating Temperature:-25°C~+85°C
- Contact Resistance:3.0mΩ max.
- Insulation Resistance:5000MΩ Min.
- Withstanding Voltage:2200V AC/minute
- Material:Housing:Nylon66 UL94V-2  
Terminal:Copper Alloy
- Finish:Tin-plated or gold plated over nickle.
- Wire Size:AWG#18~#24
- Housing Feature:Closed End
- Terminal Retention to Housing:3.63kg minimum
- UL File No:E304945
- Patent No:200620059354.4

Shenzhen Hongru Connector Co., Ltd

Email: yukyli@hrb-connector.com  
 Tel: 86-0755- 2709 6669  
 Fax: 86-0755-2709 2392  
 Skype: haiyuncheng-vivian  
 Mobile(Whatsapp): 86-186 8112 3590  
 Website: <http://www.hrb-connector.com>



C	Color	Wire size
N	Natural	AWG#18
O	Orange	AWG#18
Y	Yellow	AWG#20
R	Red	AWG#22
W	White	AWG#24

## Ordering Information And Dimensions

Part NO.		Dimensions		Part NO.		Dimensions		Part NO.		Dimensions	
TYP UL94V-2	Circuits	Dim:A	Dim:B	TYP UL94V-2	Circuits	Dim:A	Dim:B	TYP UL94V-2	Circuits	Dim:A	Dim:B
M7060R-2-C	2	7.92	3.96	M7060R-10-C	10	39.80	35.64	M7060R-18-C	18	71.08	67.32
M7060R-3-C	3	11.88	7.92	M7060R-11-C	11	43.41	39.60	M7060R-19-C	19	75.04	71.28
M7060R-4-C	4	15.84	11.88	M7060R-12-C	12	47.37	43.56	M7060R-20-C	20	78.90	75.24
M7060R-5-C	5	19.80	15.84	M7060R-13-C	13	51.33	47.52	M7060R-21-C	21	82.26	79.20
M7060R-6-C	6	23.76	19.80	M7060R-14-C	14	55.29	51.48	M7060R-22-C	22	86.82	83.16
M7060R-7-C	7	27.72	23.76	M7060R-15-C	15	59.35	55.44	M7060R-23-C	23	90.78	87.12
M7060R-8-C	8	31.68	27.72	M7060R-16-C	16	63.31	59.40	M7060R-24-C	24	94.74	91.08
M7060R-9-C	9	35.64	31.68	M7060R-17-C	17	67.12	63.36				

